

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2	(spindle adj3 motor\$2) and shaft and (rotor\$2 same (hole\$2 or opening\$2)) and ((surface\$2 near6 rotor\$2) same ((layer\$2 or material\$2) near20 treat\$3)) and (anti\$3slid\$4 or (anti adj3 slid\$4))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:41
L2	2230	310/67R.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:16
L3	55059	spindle adj3 motor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:16
L4	380	I2 and I3	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:17
L5	25	720/701.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:39
L6	405	I4 or I5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:17
L7	71	(spindle adj3 motor\$2) and ((material or layer\$2) adj20 ((mount\$3 or on or attach\$3) near10 rotor))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/03/03 21:43